



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 00135

**Product Name** Race Pro Engine Degreaser

**Recommended Use** Engine Degreaser - Aerosol

**Details of the supplier of the safety data sheet**

**Supplier Name** Race Pro Products

**Supplier Address** 2101 E Cooley  
Colton, CA  
92324

**Supplier Phone Number** Phone: (800) 657-4811

**Emergency telephone number** 1-800-535-5053

**Company Emergency Phone Number** 1-800-633-9576

## 2. HAZARDS IDENTIFICATION

### Classification


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

|                                   |            |
|-----------------------------------|------------|
| Skin corrosion/irritation         | Category 2 |
| Serious eye damage/eye irritation | Category 1 |
| Carcinogenicity                   | Category 2 |

Flammable Aerosols

Category 2

**GHS Label elements, including precautionary statements****Emergency Overview**

|   |                       |              |
|---|-----------------------|--------------|
| <b>Signal word</b>  | <b>Danger</b>         |              |
| <b>Hazard Statements</b><br>Causes skin irritation<br>Causes serious eye damage<br>Suspected of causing cancer<br>Flammable aerosol |                       |              |
|    |                       |              |
| <b>Appearance</b>   | <b>Physical state</b> | <b>Odor</b>  |
| White   | Liquid spray Aerosol  | Naphthalenic |

**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Pressurized container: Do not pierce or burn, even after use  
 Do not spray on an open flame or other ignition source

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician

**Skin**

IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation occurs: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse

**Precautionary Statements - Storage**

Store locked up  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity**

13.75% of the mixture consists of ingredient(s) of unknown toxicity

**Other information**

Toxic to aquatic life with long lasting effects

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

**Interactions with Other Chemicals**

Use of alcoholic beverages may enhance toxic effects.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                       | CAS No     | Weight-% | Trade Secret |
|-------------------------------------|------------|----------|--------------|
| Naphtha (petroleum), heavy aromatic | 64742-94-5 | 10 - 30  | *            |
| Dipropylene glycol monomethyl ether | 34590-94-8 | 10 - 30  | *            |
| Oleic acid                          | 112-80-1   | 10 - 30  | *            |
| Propane                             | 74-98-6    | 3 - 7    | *            |
| Butane                              | 106-97-8   | 3 - 7    | *            |
| Potassium hydroxide                 | 1310-58-3  | 1 - 5    | *            |
| Triethanolamine                     | 102-71-6   | 1 - 5    | *            |
| Diethanolamine                      | 111-42-2   | 0.1 - 1  | *            |

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

**First aid measures****General Advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Seek immediate medical attention/advice.

**Skin contact**

Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

**Inhalation**

Remove to fresh air. Get medical attention immediately if symptoms occur.

**Ingestion**

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

**Self-protection of the first aider** Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**Most important symptoms and effects, both acute and delayed**

**Most Important Symptoms and Effects** Burning sensation.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

**Unsuitable extinguishing media**

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

**Specific hazards arising from the chemical**

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

**Uniform Fire Code**

Irritant: Liquid  
Aerosols: Level III

**Explosion Data**

**Sensitivity to Mechanical Impact** Yes.

**Sensitivity to Static Discharge** Yes.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. See section 8 for more information. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges.

**Other Information** Refer to protective measures listed in Sections 7 and 8. Ventilate the area.

### Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Refer to protective measures listed in Sections 7 and 8. Prevent product from entering drains.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Use only with adequate ventilation and in closed systems. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Do not stick pin or any other sharp object into opening on top of can.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

**Incompatible Products** Strong acids. Strong oxidizing agents. Strong bases.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION



**Control parameters****Exposure Guidelines**

| Chemical Name                                     | ACGIH TLV  | OSHA PEL   | NIOSH IDLH  |
|---|--|--|---|
| Dipropylene glycol monomethyl ether<br>34590-94-8 | STEL: 150 ppm<br>TWA: 100 ppm<br>S*                            | TWA: 100 ppm<br>TWA: 600 mg/m <sup>3</sup><br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 600 mg/m <sup>3</sup><br>(vacated) STEL: 150 ppm<br>(vacated) STEL: 900 mg/m <sup>3</sup><br>(vacated) S*<br>S* | IDLH: 600 ppm<br>TWA: 100 ppm<br>TWA: 600 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 900 mg/m <sup>3</sup> |
| Propane<br>74-98-6                                | TWA: 1000 ppm  | TWA: 1000 ppm<br>TWA: 1800 mg/m <sup>3</sup>   | IDLH: 2100 ppm<br>TWA: 1000 ppm<br>TWA: 1800 mg/m <sup>3</sup>  |
| Butane<br>106-97-8                                | STEL: 1000 ppm   | (vacated) TWA: 800 ppm<br>(vacated) TWA: 1900 mg/m <sup>3</sup>  | TWA: 800 ppm<br>TWA: 1900 mg/m <sup>3</sup>   |
| Potassium hydroxide<br>1310-58-3                  | Ceiling: 2 mg/m <sup>3</sup>                                   | (vacated) Ceiling: 2 mg/m <sup>3</sup>   | Ceiling: 2 mg/m <sup>3</sup>  |
| Triethanolamine<br>102-71-6                       | TWA: 5 mg/m <sup>3</sup>                                       | -  |   |
| Diethanolamine<br>111-42-2                        | TWA: 1 mg/m <sup>3</sup> inhalable fraction<br>and vapor<br>S* | (vacated) TWA: 3 ppm<br>(vacated) TWA: 15 mg/m <sup>3</sup>  | TWA: 3 ppm<br>TWA: 15 mg/m <sup>3</sup>   |

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

**Appropriate engineering controls****Engineering Measures**

Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tight sealing safety goggles.

**Skin and body protection**

Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

**Respiratory protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene Measures**

Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical and Chemical Properties**

|                       |                          |                       |                          |
|-----------------------|--------------------------|-----------------------|--------------------------|
| <b>Physical state</b> | Liquid spray, Aerosol    | <b>Odor</b>           | Naphthalenic             |
| <b>Appearance</b>     | White                    | <b>Odor Threshold</b> | No information available |
| <b>Color</b>          | No information available |                       |                          |

| <u>Property</u>                        | <u>Values</u>     | <u>Remarks</u> | <u>Method</u> |
|--|-------------------|----------------|---------------|
| pH                                     | UNKNOWN           | None known     |               |
| Melting / freezing point               | No data available | None known     |               |
| Boiling point / boiling range          | No data available | None known     |               |
| Flash Point                            | No data available | None known     |               |
| Evaporation Rate                       | No data available | None known     |               |
| Flammability (solid, gas)              | No data available | None known     |               |
| Flammability Limit in Air              |                   |                |               |
| Upper flammability limit               | No data available |                |               |
| Lower flammability limit               | No data available |                |               |
| Vapor pressure                         | No data available | None known     |               |
| Vapor density                          | No data available | None known     |               |
| Specific Gravity                       | 1.01              | None known     |               |
| Water Solubility                       | Soluble in water  | None known     |               |
| Solubility in other solvents           | No data available | None known     |               |
| Partition coefficient: n-octanol/water | No data available | None known     |               |
| Autoignition temperature               | No data available | None known     |               |
| Decomposition temperature              | No data available | None known     |               |
| Kinematic viscosity                    | No data available | None known     |               |
| Dynamic viscosity                      | No data available | None known     |               |
| Explosive properties                   | No data available |                |               |
| Oxidizing properties                   | No data available |                |               |

**Other Information**

|                            |                   |
|----------------------------|-------------------|
| Softening Point            | No data available |
| VOC Content (%)            | No data available |
| Particle Size              | No data available |
| Particle Size Distribution |                   |

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong acids. Strong oxidizing agents. Strong bases.

**Hazardous Decomposition Products**

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

Product Information



|                     |   |
|---------------------|---|
| <b>Inhalation</b>   | Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.  |
| <b>Eye contact</b>  | Specific test data for the substance or mixture is not available. (based on components). Causes serious eye damage. Severely irritating to eyes. May cause irreversible damage to eyes.               |
| <b>Skin contact</b> | Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). Prolonged contact may cause redness and irritation.                                  |
| <b>Ingestion</b>    | Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |

**Component Information**

| Chemical Name                                     | Oral LD50            | Dermal LD50             | Inhalation LC50                     |
|---|----------------------|-------------------------|-------------------------------------|
| Naphtha (petroleum), heavy aromatic<br>64742-94-5 | > 5000 mg/kg ( Rat ) | > 2 mL/kg ( Rabbit )    | > 590 mg/m <sup>3</sup> ( Rat ) 4 h |
| Dipropylene glycol monomethyl ether<br>34590-94-8 | = 5230 mg/kg ( Rat ) | = 9500 mg/kg ( Rabbit ) | -                                   |
| Oleic acid<br>112-80-1                            | > 5000 mg/kg ( Rat ) | -                       | -                                   |
| Propane<br>74-98-6                                | -                    | -                       | = 658 mg/L ( Rat ) 4 h              |
| Butane<br>106-97-8                                | -                    | -                       | = 658 g/m <sup>3</sup> ( Rat ) 4 h  |
| Potassium hydroxide<br>1310-58-3                  | = 214 mg/kg ( Rat )  | -                       | -                                   |
| Triethanolamine<br>102-71-6                       | = 4190 mg/kg ( Rat ) | > 20 mL/kg ( Rabbit )   | -                                   |

**Information on toxicological effects**

**Symptoms** Erythema (skin redness). May cause redness and tearing of the eyes. May cause blindness. Burning.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Mutagenic Effects** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name               | ACGIH | IARC     | NTP | OSHA |
|-----------------------------|-------|----------|-----|------|
| Triethanolamine<br>102-71-6 |       | Group 3  |     |      |
| Diethanolamine<br>111-42-2  | A3    | Group 2B |     | X    |

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Reproductive toxicity** No information available.



|                                 |  |
|---------------------------------|--|
| <b>STOT - single exposure</b>   | No information available.  |
| <b>STOT - repeated exposure</b> | No information available.  |
| <b>Chronic Toxicity</b>         | Contains a known or suspected carcinogen.  |
| <b>Target Organ Effects</b>     | Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Nervous System (CNS). |
| <b>Aspiration Hazard</b>        | No information available.  |

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)**

6,697.00 mg/kg

**ATEmix (dermal)**

56,122.00 mg/kg (ATE)

**ATEmix (inhalation-gas)**

2,715,191.50

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects.

| Chemical Name                                     | Toxicity to Algae  | Toxicity to Fish   | Toxicity to Microorganisms | Daphnia Magna (Water Flea) |
|---|--|--|----------------------------|----------------------------|
| Naphtha (petroleum), heavy aromatic<br>64742-94-5 | 72h EC50: = 2.5 mg/L<br>(Skeletonea costatum)  | 96h LC50: = 19 mg/L<br>(Pimephales promelas) 96h<br>LC50: = 2.34 mg/L<br>(Oncorhynchus mykiss) 96h<br>LC50: = 1740 mg/L<br>(Lepomis macrochirus) 96h<br>LC50: = 45 mg/L<br>(Pimephales promelas) 96h<br>LC50: = 41 mg/L<br>(Pimephales promelas) |                            | 48h EC50: = 0.95 mg/L      |
| Dipropylene glycol monomethyl ether<br>34590-94-8 |  | 96h LC50: > 10000 mg/L<br>(Pimephales promelas)  |                            | 48h LC50: = 1919 mg/L      |
| Oleic acid<br>112-80-1                            |  | 96h LC50: = 205 mg/L<br>(Pimephales promelas)  |                            |                            |
| Potassium hydroxide<br>1310-58-3                  |  | 96h LC50: = 80 mg/L<br>(Gambusia affinis)  |                            |                            |
| Triethanolamine<br>102-71-6                       | 96h EC50: = 169 mg/L<br>(Desmodesmus subspicatus) 72h EC50: =<br>216 mg/L (Desmodesmus subspicatus)                | 96h LC50: 10600 - 13000<br>mg/L (Pimephales promelas)<br>96h LC50: > 1000 mg/L<br>(Pimephales promelas) 96h<br>LC50: 450 - 1000 mg/L<br>(Lepomis macrochirus)  |                            | 24h EC50: = 1386 mg/L      |
| Diethanolamine<br>111-42-2                        | 72h EC50: = 7.8 mg/L<br>(Desmodesmus subspicatus) 96h EC50: 2.1<br>- 2.3 mg/L<br>(Pseudokirchneriella subcapitata) | 96h LC50: 4460 - 4980<br>mg/L (Pimephales promelas)<br>96h LC50: 1200 - 1580<br>mg/L (Pimephales promelas)<br>96h LC50: 600 - 1000 mg/L<br>(Lepomis macrochirus)   |                            | 48h EC50: = 55 mg/L        |

### Persistence and Degradability

No information available.

### Bioaccumulation

| Chemical Name                                     | Log Pow |
|---|---------|
| Naphtha (petroleum), heavy aromatic<br>64742-94-5 | 6.1     |
| Dipropylene glycol monomethyl ether<br>34590-94-8 | -0.064  |
| Propane<br>74-98-6                                | 2.3     |
| Butane<br>106-97-8                                | 2.89    |
| Potassium hydroxide<br>1310-58-3                  | 0.83    |
| Triethanolamine<br>102-71-6                       | -2.53   |
| Diethanolamine<br>111-42-2                        | -2.18   |

### Other adverse effects

No information available.

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

|                               |   |
|-------------------------------|---|
| <b>Disposal methods</b>       | This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). |
| <b>Contaminated Packaging</b> | Dispose of contents/containers in accordance with local regulations.                            |
| <b>US EPA Waste Number</b>    | D001  |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name                    | California Hazardous Waste |
|----------------------------------|----------------------------|
| Potassium hydroxide<br>1310-58-3 | Toxic<br>Corrosive         |

### 14. TRANSPORT INFORMATION

#### DOT

|  |                           |
|--|---------------------------|
| <b>Proper Shipping Name</b>            | CONSUMER COMMODITY        |
| <b>Hazard Class</b>                    | 2.1                       |
| <b>Description</b>                     | CONSUMER COMMODITY, ORM-D |
| <b>Emergency Response Guide Number</b> | 126                       |

#### TDG

|                             |                       |
|-----------------------------|-----------------------|
| <b>UN-No.</b>               | UN1950                |
| <b>Proper Shipping Name</b> | AEROSOLS              |
| <b>Hazard Class</b>         | 2.1                   |
| <b>Description</b>          | UN1950, AEROSOLS, 2.1 |

#### MEX

|                             |                       |
|-----------------------------|-----------------------|
| <b>UN-No.</b>               | UN1950                |
| <b>Proper Shipping Name</b> | AEROSOLS              |
| <b>Hazard Class</b>         | 2.1                   |
| <b>Description</b>          | UN1950 AEROSOLS, 2.1, |

#### ICAO

|                             |                       |
|-----------------------------|-----------------------|
| <b>UN-No.</b>               | UN1950                |
| <b>Proper Shipping Name</b> | AEROSOLS              |
| <b>Hazard Class</b>         | 2.1                   |
| <b>Description</b>          | UN1950, AEROSOLS, 2.1 |

#### IATA

|                             |                                  |
|-----------------------------|----------------------------------|
| <b>UN-No.</b>               | UN1950                           |
| <b>Proper Shipping Name</b> | AEROSOLS, FLAMMABLE              |
| <b>Hazard Class</b>         | 2.1                              |
| <b>Description</b>          | UN1950, AEROSOLS, FLAMMABLE, 2.1 |

#### IMDG/IMO

|                             |          |
|-----------------------------|----------|
| <b>UN-No.</b>               | UN1950   |
| <b>Proper Shipping Name</b> | AEROSOLS |
| <b>Hazard Class</b>         | 2.1      |
| <b>EmS-No.</b>              | F-D, S-U |



Description UN1950, AEROSOLS, 2.1

**RID**

UN-No. UN1950  
 Proper Shipping Name AEROSOLS  
 Hazard Class 2.1  
 Classification code 5F  
 Description UN1950 AEROSOLS, 2.1,

**ADR**

UN-No. UN1950  
 Proper Shipping Name AEROSOLS  
 Hazard Class 2.1  
 Classification code 5F  
 Tunnel restriction code (D)  
 Description UN1950 AEROSOLS, 2.1,

**ADN**

UN-No. UN1950  
 Proper Shipping Name AEROSOLS  
 Hazard Class 2.1  
 Classification code 5F  
 Special Provisions 190, 327, 625  
 Description UN1950 AEROSOLS, 2.1,  
 Hazard Labels 2.1  
 Limited Quantity LQ2  
 Ventilation VE01, VE04

## 15. REGULATORY INFORMATION

**International Inventories**

TSCA Complies  
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name             | CAS No   | Weight-% | SARA 313 - Threshold Values % |
|---------------------------|----------|----------|-------------------------------|
| Diethanolamine - 111-42-2 | 111-42-2 | 0.1 - 1  | 1.0                           |

**SARA 311/312 Hazard Categories**

Acute Health Hazard Yes  
 Chronic Health Hazard Yes  
 Fire Hazard Yes  
 Sudden release of pressure hazard Yes  
 Reactive Hazard No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------|-----------------------------|------------------------|---------------------------|----------------------------|
|               |                             |                        |                           |                            |



|                                  |         |  |  |   |
|----------------------------------|---------|--|--|---|
| Potassium hydroxide<br>1310-58-3 | 1000 lb |  |  | X |
|----------------------------------|---------|--|--|---|

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name                    | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ  |
|----------------------------------|--------------------------|------------------------------------|---|
| Potassium hydroxide<br>1310-58-3 | 1000 lb                  |                                    | RQ 1000 lb final RQ<br>RQ 454 kg final RQ |
| Diethanolamine<br>111-42-2       | 100 lb                   |                                    | RQ 100 lb final RQ<br>RQ 45.4 kg final RQ |

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals.

| Chemical Name             | California Proposition 65 |
|---------------------------|---------------------------|
| Diethanolamine - 111-42-2 | Carcinogen                |

**U.S. State Right-to-Know Regulations**

| Chemical Name                                     | New Jersey | Massachusetts | Pennsylvania | Rhode Island | Illinois |
|---|------------|---------------|--------------|--------------|----------|
| Dipropylene glycol monomethyl ether<br>34590-94-8 | X          | X             | X            | X            | X        |
| Oleic acid<br>112-80-1                            |            |               | X            |              |          |
| Butane<br>106-97-8                                | X          | X             | X            |              |          |
| Propane<br>74-98-6                                | X          | X             | X            |              |          |
| Potassium hydroxide<br>1310-58-3                  | X          | X             | X            | X            |          |
| Triethanolamine<br>102-71-6                       | X          | X             | X            |              |          |
| Diethanolamine<br>111-42-2                        | X          | X             | X            | X            | X        |

**International Regulations****Mexico****National occupational exposure limits**

| Component   | Carcinogen Status | Exposure Limits   |
|---|-------------------|---|
| Dipropylene glycol monomethyl ether<br>34590-94-8 ( 10 - 30 ) |                   | Mexico: TWA 100 ppm<br>Mexico: TWA 60 mg/m <sup>3</sup><br>Mexico: STEL 150 ppm<br>Mexico: STEL 900 mg/m <sup>3</sup> |
| Butane<br>106-97-8 ( 3 - 7 )                                  |                   | Mexico: TWA 800 ppm<br>Mexico: TWA 1900 mg/m <sup>3</sup>   |

Mexico - Occupational Exposure Limits - Carcinogens

**Canada****WHMIS Hazard Class**

Not determined

**16. OTHER INFORMATION**

|             |                           |                       |                          |  |
|-------------|---------------------------|-----------------------|--------------------------|--|
| <b>NFPA</b> | <b>Health Hazards</b> 3   | <b>Flammability</b> 3 | <b>Instability</b> 0     | <b>Physical and Chemical Hazards - Personal Protection</b> |
| <b>HMIS</b> | <b>Health Hazards</b> 3 * | <b>Flammability</b> 3 | <b>Physical Hazard</b> 0 |  |



X

**Chronic Hazard Star Legend** \* = Chronic Health Hazard

|                      |  |
|----------------------|--|
| <b>Prepared By</b>   | Product Stewardship<br>23 British American Blvd.<br>Latham, NY 12110<br>1-800-572-6501 |
| <b>Issuing Date</b>  | 01-Jun-2015  |
| <b>Revision Date</b> | 01-Jun-2015  |
| <b>Revision Note</b> | No information available   |

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**